



Details are INDICATIVE ONLY and need to be made project specific.

While reasonable care has been taken to ensure that the information included in this drawing was accurate at the time of issue, we reserve the right to change specifications at any time. Final detailing remains the responsibility of the designer due to site & client specific requirements.

Do not scale from this drawing.

Drawing to be read in conjunction with all standard series drawings

1000mm Wide Alkali Resistant Mesh Centered Along Intersecting Walls and Floors

Depth of Tradical® Hemcrete® to suit thermal performance required

All structural fasteners to be non-ferrous, any galvanized fasteners to be painted with red oxide primer or bitumen paint.

5/8" Baunit FL68 Lime Render direct to Tradical® Hemcrete®

External Finish:  
1/8" Pre-colored Baunit SEP Lime Render Top Coat

Wall thickness (in.) Vs. R-value (ft <sup>2</sup> ·F·h/Btu)		
Approx. Wall Thickness	Hemcrete Thickness	Overall R-Value
11.25	10	26*
13.25	12	30*
16.25	15	35*

\*Static R-value not adjusted for thermal mass or location

Good perimeter drainage required

12.11	US Conversion	US Conversion	DWN	CKD
	ALT]TradHem]Render]MULTI_WALL_SECT	LT_H_1_06_SUF	JK	DW